



Lexicon® BD-30 Player



Lexicon® BD-30 Player

Providing unparalleled video quality, the BD-30 incorporates Anchor Bay's award-winning Video Reference Series (VRS) technology, and delivers a picture that is cleaner, smoother, true-to-life and free of artifacts. With exceptional picture and sound quality along with fast loading & response times, the BD-30 delivers an incredible sound stage and an immersive surround experience.

Features

- Complete Media Support: Blu-ray Disc, BonusVIEW, BD-Live™, DVD Up-Conversion, DVD-Audio, SACD, and Additional Media Formats
- Unparalleled Video Quality: VRS™ by Anchor Bay, Full HD 1080p Output, True 24p™ Video, Source Direct Mode, Multiple Zoom Modes, and HDMI
- High Fidelity Audio: Dolby® TrueHD, DTS®-HD, 7.1-Channel Analog Output, Dedicated Stereo Output, and Digital Optical and Coaxial Outputs
- Ultimate Convenience: Dual USB Ports, PAL/NTSC Conversion, Back-lit Remote Control, Universal Power Supply, External IR, RS232 Control, and HDMI CEC

Specifications

Disc Types*	BD-Video, DVD-Video, AVCHD, DVD-Audio, SACD, CD, HDCD, Kodak Picture CD, CD-R/RW, DVD±R/RW, DVD±R DL, BD-R/RE
BD Profile:	BD-ROM Version 2 Profile 2 (also compatible with Profile 1 Version 1.0 and 1.1)
Internal Storage:	1GB (Actual available storage varies due to system usage)

Output

Analog Audio:	7.1ch or 5.1ch, stereo
Digital Audio:	Coaxial, Optical
HDMI Audio:	Stereo, up to 7.1ch high-resolution PCM, up to 5.1ch DSD, bitstream or LPCM conversion of Dolby Digital, Dolby Digital Plus, Dolby TrueHD, DTS, DTS-HD High Resolution Audio, and DTS-HD Master Audio.
Analog Video:	Composite, Component Video (Y/Pb/Pr, 480i/480p, 720p/1080i available for non-restricted content only)
Digital Video:	HDMI with HDCP (NTSC: 480i/480p/720p/1080i/1080p/1080p24, PAL 576i/576p/720p/1080i/1080p/1080p24)

Video Characteristics

Composite Video Amplitude:	1.0Vp-p (75Ω)
Component Video:	Y: 1.0Vp-p (75Ω), Pb/Pr: 0.7Vp-p (75Ω)

Audio Characteristics* *

Frequency:	20Hz - 20kHz (±0.4dB)
Signal-to-Noise Ratio:	>110dB (A-weighted)
THD+N:	< 0.002% (1kHz at 0dBFS, 20kHz LPF)

General Specification

Power Supply:	~ 100V - 240V, 50/60Hz AC
Power Consumption:	35W (0.5W Standby)
Dimensions:	430mm x 336mm x 77mm, 16-7/8 x 13-1/4 x 3 inches
Mass:	5.1kg / 11.2 lbs
Operating Temperature:	5°C - 35°C / 41°F - 95°F
Operating Humidity:	15% - 75% No condensation

* Compatibility with user-encoded contents or user-created discs is on a best-effort basis with no guarantee due to the variation of media, software and techniques used. ** Nominal specification.

 Harman International

© 2009 Harman International Industries, Incorporated. All rights reserved.

1718 West Mishawaka Road
Elkhart, Indiana 46517 U.S.A.
516.594.0300 • lexicon.com



Lexicon and the Lexicon logo are trademarks of Harman International Industries, Incorporated, in the United States and/or other countries. Features, specifications and appearance are subject to change without notice.